

# SyncServer S600

High-Performance, Enhanced Security Network Time Server



## Features

- Ultra-high bandwidth NTP time server
- Stratum 1 operation via GNSS satellites
- Four standard GbE ports, all with patented NTP hardware timestamping
- Built-in DoS detection and protection
- Security-hardened NTP Reflector™ with firewall protection
- Web-based management with high-security cipher suite
- Exceptional time accuracy to UTC
- Extended environmental specifications
- TACACS+, RADIUS, LDAP, and more
- IPv6/IPv4 on all ports
- Rubidium atomic clock or OCXO oscillator upgrades
- Dual power supply option
- GLONASS/BeiDou/SBAS option
- PTP grandmaster option

## Applications

- Synchronizes hundreds of thousands of NTP clients
- Security-hardened for peace-of-mind time service operations
- Multiple GbE NTP ports for easy network configuration and adaptation
- Best-in-class time accuracy for improved log file timestamp precision and usability
- Very reliable and easy-to-use network time appliance for modern networks and business operations

## Best in Class

Modern networks require accurate, secure, and reliable time services, as provided by the Microsemi SyncServer S600. The security-hardened S600 network time server is purpose-built to deliver exact hardware-based Network Time Protocol (NTP) timestamps. The unparalleled accuracy and security is rounded out with outstanding ease-of-use features for reliable network time services ready to meet user network and business operation needs today and in the future.

## High Security and Capacity

The four standard GbE ports combined easily handle more than 10,000 NTP requests per second using hardware timestamping and compensation. All traffic to the S600 CPU is bandwidth-limited for protection against denial-of-service (DoS) attacks.

For significantly more robust and secure NTP operations, enable the security-hardened NTP Reflector™ with 100% hardware-based NTP packet processing capable of 360,000 NTP requests per second. The Reflector also works with the CPU-protecting firewall, with bandwidth limiting all non-NTP traffic. Coupled with the Reflector is DoS detection, notification, and protection against abnormally high network traffic. The NTP Reflector™ processes all packets at GbE line speed, thereby making it resistant to the level of network traffic that could be delivered in a DoS attack.

Security is an inherent part of the SyncServer S600 architecture. In addition to standard security features related to web interface hardening, NTP operations, and to server access, unsecure access protocols are deliberately omitted from the S600 while remaining services can be disabled. Advanced authentication services such as TACACS+, RADIUS, and LDAP are optionally available.

## Timing and Design Reliability

The 72-channel GNSS receiver, coupled with Microsemi's patented Active Thermal Compensation Technology, provides best-in class timing accuracy of <15 ns RMS to UTC. Backstop this with a durable hardware design subjected to severe shock and vibration testing, and high-reliability components that extend the operating temperature range to -20 °C to 65 °C. Further, choose the dual power supply option with SNMP trap enabled monitoring to avoid time service interruptions. As with all Microsemi time servers, upgrading to a high performance oscillator, such as a Rubidium atomic clock, keeps the S600 accurate for a long time in the event of a GNSS service disruption.

## Leverage Built-In Hardware


The SyncServer S600 includes additional built-in hardware features enabled through software license keys, such as the security-hardened NTP Reflector™, GLONASS/BeiDou support, and IEEE1588 PTP operations. The SyncServer S600, the future of time server operations, today.

# SyncServer S600

## High-Performance, Enhanced Security Network Time Server

### Four GbE Ports for Performance, Flexibility, and Security

The S600 has four dedicated and isolated GbE Ethernet ports, each equipped with NTP hardware timestamping. These are connected to a high-speed microprocessor with microsecond accurate timestamps to assure high-bandwidth NTP performance. This exceeds the need of servicing 10,000 NTP requests per second with no degradation in timestamp accuracy.




*The four GbE ports provide network configuration flexibility and enhanced security. Multiple isolated and synchronized time servers can also be configured.*

Multiple ports provide the flexibility to adapt to different network topologies as networks grow and change. A S600 can be the single time source to synchronize clients on different subnets and physical networks. There is only one time reference, but it can appear as though there are four clocks available because each port is independent.

NTP can be served on all four ports. The highly secure web-based management interface is only available on port 1 so that administrators may choose to keep that IP address private and secure. Unique access control lists for each port can govern server response to client requests for time.

### Intuitive, Secure, and Easy-to-Use Web Interface

The modern web interface is the primary control interface of the S600. Once the keypad and display bring the unit online, complete status and control functions are easily found via the well-organized left navigation menu.



*At-a-glance dashboard presentation combined with logical organization and intuitive controls that make configuring the S600 easy.*

### Standard Management Access Security

All of the expected network management protocols are standard in the S600. This include mandatory password access, HTTPS/SSL only (using the high encryption cipher suite), SSH, access control lists, service termination, SNMPv2/v3, and NTP MD5 authentication. All traffic to the S600 CPU is bandwidth-limited for protection against DoS attacks. The local keypad on the server can be password-protected to prevent tampering.

### Security-Hardening Option

The SyncServer S600 can be seriously hardened from both an NTP perspective and an authentication perspective through the Security Protocol license option, which includes the security-hardened NTP Reflector.

**Operational Hardening**— via the 360,000 NTP packet per second NTP Reflector™ with 100% hardware based NTP packet processing that also works with a CPU-protecting firewall by bandwidth limiting all non-NTP traffic. The Reflector also monitors packet flow for DoS detection and reporting, yet remains impervious to the level of network traffic as it operates at line speed.

**Authentication Hardening**— is available for NTP client or server authentication through the NTP Autokey function or user access authentication via TACACS+, RADIUS, and LDAP. Third party CA-signed X.509 certificates are installable for further hardening of management access. (See the [SyncServer Options datasheet](#) for more detail on the Security Protocol License Option.)



*An entire drop down menu in the S600 dedicated to security-related protocols*

# SyncServer S600

## High-Performance, Enhanced Security Network Time Server

### Unprecedented NTP Accuracy

The Stratum 1 level S600 derives nanosecond accurate time directly from the atomic clocks aboard the GNSS satellites. By using an integrated, 72-channel global navigation satellite system (GNSS) receiver, every visible satellite can be tracked and used to maintain accurate and reliable time. Even in urban canyon environments where direct satellite visibility can be limited, manually inputting the position can be sufficient to acquire accurate time even from a single intermittent satellite.

### Ultra-High Performance NTP

The S600 can effortlessly support hundreds of thousands of network clients while maintaining microsecond-caliber NTP timestamp accuracy. NTP request throughput rates exceed 10,000 requests/second while maintaining NTP timestamp accuracy. If the Security License option is enabled, the NTP Reflector™ can process over 360,000 NTP requests per second with 15 ns caliber timestamp accuracy with the added benefit of security hardening the network port. This can easily translate into sub-millisecond typical NTP client synchronization accuracy on a LAN.

### Peering and Holdover

If the GNSS reference signal is lost entirely, the S600 can automatically revert to retrieving time from other user-designated internal or external network time servers. This technology, known as peering, prevents disruption of time service to the network, as the network administrator is notified immediately of the change in time reference status and stratum via SNMP.

A popular adjunct to peering is letting the time server operate in holdover (also called free run or flywheel), where the clock in the time server is allowed to drift if the GNSS signal is lost. The user can specify how far to let the clock drift in terms of estimated time accuracy before reverting to peering. If the optional Rubidium atomic clock is installed, the S600 can flywheel for weeks and still be accurate to less than a millisecond.

### Multi-GNSS Constellation Support for Enhanced Reliability

Timing integrity, continuity, and reliability can be improved with the multi-GNSS constellation license that adds support for GLONASS, BeiDou, and SBAS constellations in addition to the standard GPS constellation. With more satellites in view, timing performance can be improved in challenging environments, such as urban canyons. All SyncServer S600's ship with GNSS hardware ready to be enabled with a software license.

### Time Cross-Checking for Peace-of-Mind Reliability

The S600 can time cross-check GNSS against at least two other time servers. This protects against an improperly operating GNSS receiver that can subtly corrupt the time. It also serves as a form of spoofing protection.

### IEEE1588 PTP Grandmaster

Applications demanding precise time accuracy can benefit from the IEEE1588 Precise Time Protocol (PTP). The S600 PTP Output license enables PTP grandmaster operations leveraging the built-in hardware timestamping on each LAN port of the S600. (See the [SyncServer Options datasheet](#) for more detail on the PTP Output option.)



### Oscillator Upgrades Improve Holdover Accuracy and Save Valuable Time

The standard S600 is equipped with a crystal oscillator that keeps the S600 accurate to nanoseconds when tracking GNSS. However, if GNSS connectivity is lost, thereby placing the server in holdover, the oscillator will begin to drift and impact timing accuracy. Upgrading the oscillator improves the holdover accuracy significantly. For example, consider the following drift rates for the standard oscillator compared to the OCXO and Rubidium upgrades:

#### Oscillator Holdover Drift

(1<sup>st</sup> 24 hours)

- Standard 400 microseconds
- OCXO 25 microseconds
- Rubidium <1 microsecond

The value of the upgraded oscillator is that if the GNSS signal is lost, the S600 can continue to serve very accurate NTP time. This provides the IT staff plenty of time to correct the problem with no degradation or disruption in network time synchronization accuracy.



### Serial Time Outputs

The dedicated data/timing port is provided to output NMEA-0183 or NENA PSAP strings. If NENA is selected, the serial console port also supports the two-way timing aspects of the standard. The F8 and F9 Microsemi legacy time strings are also available.

# SyncServer S600

## High-Performance, Enhanced Security Network Time Server

### Specifications

#### GNSS Receiver/Antenna

- 72 parallel channel GNSS receiver
- GPS time traceable to UTC (USNO)
- Acquisition time of 30 seconds (cold start)
- Cable length up to 900 feet (275 m). See options below.
- GNSS option adds GLONASS/BeiDou/SBAS support in addition to GPS

#### Time Accuracy

- <15 ns RMS to UTC (USNO) at 1PPS output

After one day locked to GPS; evaluated over normal environment (test range <math>\pm 5^{\circ}\text{F}</math> defined in GR-2830)

#### Oscillator Aging (monthly)

| Oscillator                              | Aging                   |
|---|-------------------------|
| Standard                                | $\pm 1 \times 10^{-7}$  |
| OCXO                                    | $\pm 5 \times 10^{-9}$  |
| Rb                                      | $\pm 1 \times 10^{-10}$ |
| After one month of continuous operation |                         |

#### Holdover Accuracy (one day)

| Oscillator   | Time              |
|--|-------------------|
| Standard   | 400 $\mu\text{s}$ |
| OCXO   | 25 $\mu\text{s}$  |
| Rb   | <1 $\mu\text{s}$  |
| Evaluated over normal environment (test range <math>\pm 5^{\circ}\text{F}</math> defined in GR-2830 after three days locked to GNSS) |                   |

#### Frequency Output Accuracy and Stability

- Frequency output accuracy <math>< 1 \times 10^{-12}</math> at one day locked to GNSS

#### Network Protocols

|                                |  |
|--------------------------------|--|
| NTP (SHA1, Autokey, MD5), SNTP | SSHv2  |
| PTP                            | IPv4/IPv6  |
| SNMP v2c, v3                   | Syslog 1 to 8 servers                                  |
| Custom MIB                     | Key management protocols can be individually disabled. |
| DHCP/DHCPv6                    | Port 1: Management and time protocols                  |
| TACACS+                        | Port 2, 3, and 4: Time protocols only                  |
| LDAPv3                         | X.509 HTTPS certificates                               |
| RADIUS                         |  |
| HTTPS/SSL* (TLS 1.1/1.2)       |  |
| SMTP forwarding                |  |

\*SSL\_High\_Encryption Cypher suite or the SSL\_High\_And\_Medium\_Encryption Cypher suite

#### NTP Server Performance

- 10,000 NTP requests per second while maintaining accuracy associated with reference time source.
- Stratum 1 via GNSS: overall server timestamp accuracy of 5 microseconds to UTC with 1-sigma variation of 15 microseconds (typical). All NTP timestamps are hardware-based or have real-time hardware compensation for internal asymmetric delays. The accuracy is inclusive of all NTP packet delays in and out of the server, as measured at the network interface. NTP serves the UTC timescale by definition, but the user can choose to serve GPS timescale instead. The SyncServer easily supports hundreds of thousands of NTP clients.
- NTP Reflector option: 360,000 NTP client mode three requests per second. NTP packets time stamped 100% in hardware with prevailing clock accuracy. All non-NTP packets are provided to the CPU on a bandwidth-limited basis. The NTP Reflector is included as part of the Security Protocol License Option.

#### Mechanical/Environmental

- Size 1.73" x 17.24" x 15.88" (4.4 cm x 43.8 cm x 40.3 cm)  
1U rack mount, including BNCs
- Power 88 VAC–264 VAC, 50 Hz–60 Hz, 65 watts  
Optional 2<sup>nd</sup> power supply
- Operating temperature Non-Rb: -20 °C to 65 °C  
Rb: -5 °C to 55 °C
- Storage temperature -40 °C to 85 °C  
(IEC 60068-2-1Ab (low temp soak), IEC 60068-2-2Bb (hi-temp soak), IEC 60068-2-14Nb (change of temp) IEC 60068-2-78Cb (humidity storage), IEC 60068-2-30Db (humidity condensation))
- Operational humidity  $\leq 95\%$ , non-condensing, IEC 60068-2-78Cb, IEC 60068-2-30Db
- Certifications FCC Part 15, Class A, CISPR 22, Class A, UL/CSA 60950-1, IEC 60950-1, EN 60950-1, PSE, VCCI, RoHS 6/6
- Server weight 12.5 lbs (5.7 kgs)
- Shipping package 16.3 lbs (7.4 kgs)
- Shock and Vibration
- Operational ETSI EN-300 019-2-3, Mil-Std-810G
- Storage IEC 60068-2-6 Fc (sinusoidal vib) Mil-Std-810G, figure 514.6C-3
- Seismic EN300 019-2-3 NEBS GR-63-CORE

# SyncServer S600

## High-Performance, Enhanced Security Network Time Server

- Transportation
  - Bounce IEC 60068-2-27Ea (shock 18 g)
  - Vibration IEC 60068-2-64Fh (random vib)
  - Package drop IEC 60068-2-31 Ec

### Front Panel

- Display Sharp, high-resolution 160x32 vacuum-fluorescent
- Keypad 0–9 numeric, up, down, left, right, ENTER, CLR, TIME, STATUS, MENU, keypad lockout.
- LEDs (tri-color green/red/orange)
  - Sync Time reference status
  - Network Network connection status
  - Alarm Fault condition

### Rear Panel

- Network Four RJ-45 100/1000Base-T Ethernet, Speed/Duplex: Auto, 100/1000 full
- Serial data/timing NMEA-0183; ZDA/GGA/GSV/RMC messages; NENA 04-002 messages; DB9-F RS-232 user-selectable rate to 115.2 kbps
- 1PPS-out BNC, Rising edge on-time, TTL into 50 Ω
- GNSS BNC L1, 1575 MHz
- Console DB9-F RS-232
- Alarm relay SPST, maximum 300 mA and 32 V
- Power IEC 60320 C14 connector, optional second power supply/connector, hitless switching.

### Options (see Options datasheet)

- Security License Upgrade option for security-hardened NTP Reflector, RADIUS, LDAP, TACACS+, NTP Autokey, X.509 certificates
- Dual power supplies (with dual-corded connectors and load sharing)
- Rubidium or OCXO oscillator upgrade for extended holdover
- GNSS support of GLONASS/BeiDou/SBAS
- IEEE1588 PTP grandmaster
- Antenna kits, cables, lightning arrestors, and inline amplifiers are documented in the SyncServer S600/S650 Options datasheet
- Domain Time II comprehensive time client, server and management software for easy distribution, management and monitoring of time across Windows networks

### Product Includes

SyncServer S600, locking power cord, and rack mount ears. Two-year hardware warranty. Current manual and MIB are available online at [www.microsemi.com](http://www.microsemi.com).

### Part Number

| Description (single power supply models)                   | Part Number   |
|--|---------------|
| SyncServer S600  | 090-15200-601 |
| SyncServer S600 with OCXO                                  | 090-15200-602 |
| SyncServer S600 with Rubidium                              | 090-15200-603 |
| Contact factory to add more options or configure-to-order. |               |

| Description (dual power supply models)                     | Part Number   |
|--|---------------|
| SyncServer S600 with dual PSU                              | 090-15200-604 |
| SyncServer S600 with OCXO and dual PSU                     | 090-15200-605 |
| SyncServer S600 with Rubidium and dual PSU                 | 090-15200-606 |
| Contact factory to add more options or configure-to-order. |               |

### SyncServer S600 Rear Panel



**Microsemi Corporate Headquarters**  
 One Enterprise, Aliso Viejo, CA 92656 USA  
 Within the USA: +1 (800) 713-4113  
 Outside the USA: +1 (949) 380-6100  
 Fax: +1 (949) 215-4996  
 Email: [sales.support@microsemi.com](mailto:sales.support@microsemi.com)  
[www.microsemi.com](http://www.microsemi.com)

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at [www.microsemi.com](http://www.microsemi.com).

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.